

## TAP FLEXIBLES DATA SHEET



Dia.1

### DESIGN & MATERIAL CONSTRUCTION

**Hose:** EPDM Rubber

**Braid:** 304 Stainless Steel

**Metal Fittings:** CW617N/CW614N

**Plastic Fittings:** Polyacetal (unfilled) & EPDM O-Ring

### DESCRIPTION

Hydrflex's tap flexibles offers a versatile and practical connection for general plumbing such as sinks, basins and toilets, with a wide variety of ready-made stock options to suit all domestic requirements. This range is also suitable for use in commercial washroom installation, these are manufactured from non toxic EPDM rubber liner with a stainless steel overbraid. Secured by hydraulically swaged ferrules with your choice of end fittings. Please note these are not suitable for use as Fan Coil hoses.

### APPLICATIONS & ADVANTAGES

- Fully Customisable at Request
- Suitable for Sinks, Basins & Toilets
- Suitable for Domestic and Commercial Washrooms
- A Misaligned Pipework Solution

### ASSEMBLY DATA

| Part Number    | Bore | Length | End Fitting 1 | End Fitting 2    |
|----------------|------|--------|---------------|------------------|
| TAP15J-3/4     | 13mm | 300mm  | 3/4" Female   | 15mm JG Speedfit |
| TAP15J-3/4-500 | 13mm | 500mm  | 3/4" Female   | 15mm JG Speedfit |
| TAP15J-3/4-900 | 13mm | 900mm  | 3/4" Female   | 15mm JG Speedfit |

### TECHNICAL

|             | Brass Fittings | John Guest & Plastic Fittings |
|-------------|----------------|-------------------------------|
| Pressure    | 15 Bar         | 10 Bar                        |
| Temperature | 70°C           | 65°C                          |

**FURTHER INFORMATION**

For any more information that you may require then please contact one of our team.

Tel: 0845 260 4334 Email: [enquiries@hydraflex.co.uk](mailto:enquiries@hydraflex.co.uk)