

TAP FLEXIBLES DATA SHEET



Dia.1

DESIGN & MATERIAL CONSTRUCTION

Hose: EPDM Rubber Braid: 304 Stainless Steel Metal Fittings: CW617N/CW614N

Plastic Fittings: Polyacetal (unfilled) & EPDM O-Ring

DESCRIPTION

Hydraflex's tap flexibles offers a versatile and practical connection for general plumbing such as sinks, basins and toilets, with a wide variety of ready-made stock options to suit all domestic requirements. This range is also suitable for use in commercial washroom installation, these are manufactured from non toxic EPDM rubber liner with a stainless steel overbraid. Secured by hydraulically swaged ferrules with your choice of end fittings. Please note these are not suitable for use as Fan Coil hoses.

APPLICATIONS & ADVANTAGES

- Fully Customisable at Request
- Suitable for Sinks, Basins & Toilets
- Suitable for Domestic and Commercial Washrooms
- A Misaligned Pipework Solution

ASSEMBLY DATA

| Part Number | Bore | Length | End Fitting 1 | End Fitting 2 |
|-------------|------|--------|------------------|------------------|
| TAP15JJ | 13mm | 300mm | 15mm JG Speedfit | 15mm JG Speedfit |

TECHNICAL

| | Brass Fittings | John Guest & Plastic Fittings |
|-------------|----------------|-------------------------------|
| Pressure | 15 Bar | 10 Bar |
| Temperature | 70°C | 65°C |

FURTHER INFORMATION

For any more information that you may require then please contact one of our team.

Tel: 0845 260 4334 Email: enquiries@hydraflex.co.uk