

TAP FLEXIBLES DATA SHEET



Dia.1

DESIGN & MATERIAL CONSTRUCTION

Hose: EPDM Rubber

Braid: 304 Stainless Steel

Metal Fittings: CW617N/CW614N

Plastic Fittings: Polyacetal (unfilled) & EPDM O-Ring

DESCRIPTION

Hydrflex's tap flexibles offers a versatile and practical connection for general plumbing such as sinks, basins and toilets, with a wide variety of ready-made stock options to suit all domestic requirements. This range is also suitable for use in commercial washroom installation, these are manufactured from non toxic EPDM rubber liner with a stainless steel overbraid. Secured by hydraulically swaged ferrules with your choice of end fittings. Please note these are not suitable for use as Fan Coil hoses.

APPLICATIONS & ADVANTAGES

- Fully Customisable at Request
- Suitable for Sinks, Basins & Toilets
- Suitable for Domestic and Commercial Washrooms
- A Misaligned Pipework Solution

ASSEMBLY DATA

Part Number	Bore	Length	End Fitting 1	End Fitting 2
TAP22J-13	13mm	300mm	3/4" Female	22mm JG Speedfit
TAP22J-13-500	13mm	500mm	3/4" Female	22mm JG Speedfit
TAP22J-13-900	13mm	900mm	3/4" Female	22mm JG Speedfit

TECHNICAL

	Brass Fittings	John Guest & Plastic Fittings
Pressure	15 Bar	10 Bar
Temperature	70°C	65°C

FURTHER INFORMATION

For any more information that you may require then please contact one of our team.

Tel: 0845 260 4334 Email: enquiries@hydraflex.co.uk