

EPB-SERIES

EPB-SERIES ELECTRIC PUMPS

▶ Features

- ◆ Covers most applications in the industry.
- ◆ High flow rate reaches 60in³/min and 120in³/min.
- ◆ 10Ft 24V, remote control or solenoid control for operator safety.
- ◆ 2.0 hp and 3.0 hp motor.
- ◆ Starts under full load.
- ◆ High strength frame with handle for maximum portability.

Reservoir Capacity

2.6, 5.3 Gallon

Flow at Rated Pressure

60, 120 in³/min

Motor

2.0,3.0hp

EPB-10B SERIES		Description	Output Flow Rate (cu.in./min)	
Used with cylinder	Model		First stage	Second stage
Single Acting	EPB-10B8P10A	2.0 hp pump with 2.6 Gallon usable oil reservoir, 3W/3P manual valve, pendant switch, 115V.	610	60
	EPB-10B2D10A	2.0 hp pump with 2.6 Gallon usable oil reservoir, 2W/2P, Solenoid valve, pendant switch, 115V.	610	60
Double Acting	EPB-10B5P10A	2.0 hp pump with 2.6 Gallon usable oil reservoir, 4W/3P manual valve, pendant switch, 115V.	610	60
	EPB-10B4D10A	2.0 hp pump with 2.6 Gallon usable oil reservoir, 4W/2P Solenoid valve, pendant switch, 115V.	610	60

EPB-20B SERIES		Description	Output Flow Rate (cu.in./min)	
Used with cylinder	Model		First stage	Second stage
Single Acting	EPB-20B8M20C	3.0 hp pump with 5.3 Gallon usable oil reservoir, 3W/3P manual valve, 230V.	610	120
Double Acting	EPB-20B5M20C	3.0 hp pump with 5.3 Gallon usable oil reservoir, 4W/3P manual valve, 230V.	610	120

EPB-SERIES



EPB- 10B4D10A



EPB- 10B5P10A

Valve	Valve Type	Valve Function	Control Switch	Motor	Usable Oil Capacity	Weight
EV-43M3	3W,3P	Advance hold/return	Remote Motor Control (10 ft)	2.0hp 115V/60 HZ	2.6 Gallon	99 lbs
EV-52H2	2W,2P	Advance Return **	Solenoid Control (10 ft)	2.0hp 115V/60 HZ	2.6 Gallon	99 lbs
EV-43M4	4W,3P	Advance hold/return	Remote Motor Control (10 ft)	2.0hp 115V/60 HZ	2.6 Gallon	99 lbs
EV-52H4	4W,2P	Advance Return **	Solenoid Control (10 ft)	2.0hp 115V/60 HZ	2.6 Gallon	99 lbs

Valve	Valve Type	Valve Function	Control Switch	Motor	Usable Oil Capacity	Weight
EV-43M3	3W,3P	Advance hold/return	Manual Control	3.0 hp,3 Phase 230V/60HZ	5.3 Gallon	132 lbs
EV-43M4	4W,3P	Advance hold/return	Manual Control	3.0 hp,3 Phase 230V/60HZ	5.3 Gallon	132 lbs

** "Advance" position holds pressure with motor shut off.