

Thermoplastic Sewer Jetting Hose**Application:**

Standard Sewer Cleaning vehicles and Sewer Cleaning equipment. Special fully bonded construction and optimum cut and wear resistance, for an increased lifetime. Cover resistant to microbiological degradation. Lightweight compared to conventional rubber sewer cleaning hoses. Available in customary length.

Application Standards:

Exitflex QD-M

Construction:

Core: Thermoplastic Elastomer

Reinforcement: EF301 single or double braid of synthetic fibre.

Cover: Polyurethane, orange colour. Special colours and private print upon request.

Temperature Standards:

-40°C to + 60°C

Thermoplastic Sewer Jetting Hose 175 bar



Technical data subject to change, Hoses to industrial standards, © 09/2012 Exitflex GmbH

Hose Type		Size	Hose I.D. (Nom.)		Hose O.D. (Nom.)		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Ref.-Nr.	Dash Size	DN	in inch	in mm	in inch	in mm	in psi	in bar	in psi	in bar	in mm	in inch
EF301-3	3	5	3/16	4,8	0,405	10,3	2.500	175	6.250	438	40	1,6
EF301-4	4	6	1/4	6,4	0,490	12,4	2.500	175	6.250	438	40	1,6
EF301-8	8	12	1/2	12,7	0,810	20,6	2.500	175	6.250	438	100	4,0
EF301-12	12	20	3/4	19,1	1,150	29,2	2.500	175	6.250	438	125	5,0
EF301-16	16	25	1	25,4	1,450	36,8	2.500	175	6.250	438	160	6,4
EF301-20	20	32	1.1/4	32,0	1,800	45,7	2.500	175	6.250	438	250	10,0