


EVA 373 AS



Antistatic suction hose; EVA $<10^{11} \Omega$, light, crush resistant, lightweight

Applications

- for domestic and industrial vacuum cleaners

Properties

- surface resistance $<10^{11} \Omega$
- crush resistant
- light model
- highly flexible
- good resistance to alkalis and acids
- good resistance to UV and ozone

- gas and liquid tight
- floatable
- light weight
- conform to RoHS guideline

Temperature Range

- -25°C to 65°C

Design, Material

1. self-supporting profile design
2. open profile geometry; wall: EVA

Delivery variants

- further diameters and lengths available on request
- black (standard)
- as a pre-assembled hose system with CONNECT connectors
- customised connectors

I.D. in / mm	O.D. mm	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Further Production Lengths m	Order No.
- / 20	26,8	0,500	42,0	0,130	-	30	373-0020-1002
1 / 25	32,2	0,500	53,5	0,150	30	-	373-0025-1002
- / 30	38,0	0,500	62,0	0,200	-	30	373-0030-1002
1,25 / 32	40,4	0,500	66,0	0,240	30	-	373-0032-1002
1,36 / 35	43,8	0,500	70,5	0,260	30	-	373-0035-1002
1,5 / 38	47,2	0,500	74,0	0,310	30	-	373-0038-1002
- / 40	49,4	0,500	80,0	0,320	30	-	373-0040-1002
1,75 / 44-45	55,0	0,500	88,5	0,370	30	-	373-0045-1002
2 / 50-51	60,4	0,500	97,0	0,440	30	-	373-0050-1002
2,36 / 60	72,0	0,500	113,0	0,670	30	-	373-0060-1002

Accessories



CLAMP 208



CONNECT 227

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.