


# CONNECT 270-271



Metal hose connector / reducer

## Properties

- easily and quickly fitted
- re-usable
- rust protected
- conform to RoHS guideline

## Temperature Range

- 200°C

## Design, Material

galvanised sheet metal

## Delivery variants

- further diameters available on request.
- Stainless Steel (INOX)

## Suitable for hose

PROTAPE®: 301, 370, 327 MEMORY; MHF: 330+331, 335 FLAT, CU 335 FLAT, INOX 330, INOX-AS 330; PVC: 310+371; TPE: 320+326 MEMORY; PE: 322 EC  
 AIRDUC®: 353+355, 350-355 MHF, 351+355 HT-PUR + EC + ExTra + INOX MHF + INOX MHF-AS; 355 CSH + REINFORCED + ORANGE; PVC:

341+345; TPE: 363; PE: 362 EC + F  
 TIMBERDUC®: 531-534, 532 CNC  
 CP: Aramid: 461+461 PROTECT; HiTex: 480-487 + 467 WELDING; HYP: 450+450 PROTECT; PE: 457+457 EC; PTFE: GLASS-INOX, 471+471 EC + HYP-INOX 472+472 EC + INOX 475 EC+F; 455 MHF; PVC: 465+465 HT; 460 SIL; 459 EC; Kapton® 476  
 NORPLAST®: 385, CU 386; PVC: 379+380 Superelastic, 380 GREEN, 383; 384; CU 384  
 NEO: 1+2  
 SIL: 1+2  
 SuperFlex PVC 372

Suitable for Hose I.D. d1	Suitable for Hose I.D. d2	Adapter length I1	Adapter length I2	Total Length I3	Wall Thickness mm	Weight kg/Pcs	Order No.
<b>Hose connector</b>							
50	50	40	40	90	0,6	0,200	270-0050-0000
60	60	40	40	90	0,6	0,200	270-0060-0000
70	70	40	40	90	0,6	0,200	270-0070-0000
75	75	40	40	90	0,6	0,200	270-0075-0000
80	80	40	40	90	0,6	0,200	270-0080-0000
90	90	40	40	90	0,6	0,200	270-0090-0000
100	100	40	40	90	0,6	0,200	270-0100-0000
110	110	40	40	90	0,6	0,300	270-0110-0000
120	120	40	40	90	0,6	0,300	270-0120-0000
125	125	40	40	90	0,6	0,300	270-0125-0000
130	130	40	40	90	0,6	0,300	270-0130-0000
140	140	40	40	90	0,6	0,400	270-0140-0000
150	150	40	40	90	0,6	0,500	270-0150-0000
160	160	40	40	90	0,6	0,500	270-0160-0000
170	170	40	40	90	0,6	0,500	270-0170-0000
175	175	40	40	90	0,6	0,600	270-0175-0000
180	180	40	40	90	0,6	0,600	270-0180-0000
200	200	40	40	90	0,6	0,600	270-0200-0000
215	215	40	40	90	0,6	0,700	270-0215-0000
225	225	40	40	90	0,6	0,700	270-0225-0000
250	250	60	60	130	0,6	0,800	270-0250-0000
275	275	60	60	130	0,6	0,900	270-0275-0000
300	300	60	60	130	0,7	1,000	270-0300-0000
315	315	60	60	130	0,7	1,100	270-0315-0000
325	325	60	60	130	0,7	1,200	270-0325-0000
350	350	60	60	130	0,7	1,300	270-0350-0000
375	375	80	80	170	0,7	1,500	270-0375-0000
400	400	80	80	170	0,7	1,600	270-0400-0000

Further technical data on [www.norres.com](http://www.norres.com). The right to make technical modifications is reserved. All values have been determined at 20°C and are approx. values.

Suitable for Hose I.D. d1	Suitable for Hose I.D. d2	Adapter length l1	Adapter length l2	Total Length l3	Wall Thickness mm	Weight kg/Pcs	Order No.
450	450	80	80	170	0,7	2,100	270-0450-0000
500	500	80	80	170	0,7	2,300	270-0500-0000

Hose reduction							
75	50	40	40	135	0,6	0,200	271-0075-0000
80	70	40	40	125	0,6	0,200	271-0080-0000
100	80	40	40	140	0,6	0,200	271-0100-0000
125	100	40	40	145	0,6	0,300	271-0125-0000
150	100	40	40	175	0,6	0,300	271-0150-0000
200	150	40	40	175	0,6	0,500	271-0200-0000
250	200	60	40	200	0,6	0,800	271-0250-0000
300	200	60	40	265	0,7	1,200	271-0300-0000
80	50	40	40	135	0,6	0,200	271-0080-2655
100	70	40	40	150	0,6	0,200	271-0100-2660
125	80	40	40	175	0,6	0,300	271-0125-2665
150	80	40	40	205	0,6	0,400	271-0150-2670
150	125	40	40	145	0,6	0,300	271-0150-2671
200	100	40	40	245	0,6	0,600	271-0200-2675
200	125	40	40	215	0,6	0,600	271-0200-2676
250	125	60	40	300	0,6	1,000	271-0250-2680
250	150	60	40	270	0,6	0,900	271-0250-2681
300	150	60	40	335	0,7	1,300	271-0300-2685
300	250	60	40	195	0,7	1,300	271-0300-2687

Further diameters available on request. All values indicated here are approximate figures based on a temperature of 20°C. Data subject to change without notice. Please also refer to our Technical Appendix on [www.norres.com](http://www.norres.com).

## Accessories



CLAMP 212



CLAMP 216



CLAMP 208



CLAMP 211



CLAMP 212 EC



CLAMP 217



CLAMP 213



CONNECT 223