

# Pneumatic Valves



## Pneumatically Piloted Technopolymer Valves, 1/8" Connection (3/2 NC & NO, 5/2 & 5/3)



**Temperature Range:**  
5°C to 50°C



**Working Pressure:**  
0 to 10 bar



3/2 Pilot/Spring



5/2 Pilot/Mech  
Spring



5/2 Pilot/Pilot

### Technical Data:

Fluid: Filtered air with or without lubrication

Operating Pressure: 0.5 to 10 bar

Reference Flow Rate: 490 NI/min

Body Size: 22mm

### Features:

- Lightweight technopolymer
- Installation, body mount
- Choice of spool assisted, for low actuation force

### Materials:

Body: Technopolymer

Spring: Stainless Steel

Seals: NBR

Spool: Nickel Plated Aluminium

Pilot Valves, BSPP			
Part code	Function	Thread	ISO Symbol
2038-6371	3/2 Pilot/Spring, Normally Closed	1/8"	
2038-6389	3/2 Pilot/Spring, Normally Open	1/8"	
2038-6397	3/2 Pilot/Pilot	1/8"	
2038-6413	5/2 Pilot/ Mech Spring	1/8"	
2038-6421	5/2 Pilot/Pilot	1/8"	
2038-6439	5/2 Pilot Priority/Pilot	1/8"	