

- The ideal pad for all those uncomfortable kneeling jobs.
- Reduces knee pain and lower back stress caused by regular kneeling.
- Lightweight to carry only 0.45kg per pad with carrier handle.
- Resistant to oils and chemicals.
- Manufactured from closed cell PVC/nitrile blend foam.

Product height: 25mm



Dimensions (m.)	Weight Kg	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
.53 x .36	1	52 x 34.5 x 2.5	Bagged	1	100	Black	KNEE-SAVER

Test Report

Type of Product: NBR Foam
Sample Recieved: 29/11/2005
Testing Date: 06/12/2005

Conclusion: The test results of Pb, Cd, Hg, Cr+6, PBB and PBDE for the submitted sample comply with the

requirements of RoHS (2002/95/EC).

Test Item (s):	Unit	Method		Result No.1	Limit of ROHS
Chromium VI (Cr+6)	ppm	UV-VIS after reference to US EPA 3060A.		N.D.	1000
Cadmium (Cd)	ppm	ICP-AES after reference to EN 1122, method B:2001 or other acid digestion.		N.D.	1000
Mercury (Hg)	ppm	ICP-AES after reference to US EPA 3052 or other acid digestion.		N.D.	1000
Lead (Pb)	ppm	ICP-AES after reference to US EPA 3050B or other acid digestion.		N.D.	1000

Continued on next page

The information contained within this datasheet is for guidance only. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed.



Note: (1) N.D. = Not detected (<MDL)

- (2) ppm = mg/kg
- (3) MDL = Method Detection Limit
- (4) " " = Not Regulstion
- (6) Decabromodiphenyl ether (DecaBDE) in polymeric applications is Commission Decision of 13 Oct 2005 amending Directive 2002/95/EC under document 2006/717/EC.
- (6) PBBEs=PBDEs=Polybrominated Diphenyl Ethers=PBDOs=PBBOs.

End of Document

The information contained within this datasheet is for guidance only. All dimensions quoted are nominal figures. Please note that some products may be subject to a degree of shrinkage when installed.

