

# EUROCEL PP 5231

## PF52 C/80 BLACK



### Description of Product

Film backing: Polyethylene film  
 Colour: Black  
 Adhesive Type: Rubber

### Technical Data

Thickness: 80µm  
 Adhesion to stainless steel: 1.3 +/- 0.4 N/cm

### Application Conditions

The surface must be free from oil, fat, dust and solvents  
 Room temperature (> 10C and < 40C)

### Resistance

Against moisture: Good  
 Against oil: Moderate  
 Against solvents: Moderate  
 Against UV: 12 months

### Storage conditions of rolls

Room temperature (> 10C and < 40C)  
 Storage time max. 6 months after date of production  
 No direct exposure to sunlight and moisture

- The low-tack adhesive allows easy unwinding from the roll, avoiding distortion of the film.
- Easy, clean removal from the protected article after use.
- Resistant to moisture, many chemicals, such as diluted acids and alkalis, and salt solutions.
- Suitable for indoors or outdoors.
- Available in all black or black back white surface, can be written on.
- Used as a protection film for the transport of window frames and ladders
- The tape performs well on mild steel, stainless steel and aluminium.



### 2903/1102 Outdoor Low-Tack Protection Tape, 100 Metre Rolls

| Part Number      | mm | Colour      |
|------------------|----|-------------|
| 2903BLACKBLACK50 | 50 | Black/Black |
| 2903BLACKBLACK75 | 75 | Black/Black |