


Fast Clean 200 & 201



Technical Data



As a substitute for 1,1,1-trichloroethane and other chlorinated solvents, Fastclean 200 immediately responds to the needs of users for all degreasing and surface preparation:-

- When a very high evaporation speed is required
- When a high KB solvent is necessary for cleansing and cleaning heavily soiled parts
- When a hydrolysis risk must be avoided

BENEFITS

- High KB factor – 106 vs 30 to 75 for other formulations. (A high KB value = more effective degreasing action)
- Extremely low surface tension – half that of 1,1,1-trichloroethane - means improved surface wetting to get under dirt more effectively

FEATURES

- Clear, low odour, cleaner that is quick drying
- Fast evaporation – leaves surface dry
- An excellent surface preparation for bonding, plating or painting
- Highly effective on all metals and most plastics and rubbers*
- Safe to use – low toxicity.

TYPICAL USES

SURFACE PREPARATION

- Cleaning metallic parts, certain plastics*, composites and elastomers
- Eliminating organic and inorganic soiling before assembly, surface treatment, bonding, painting or plating

CLEANING OPERATIONS

- Can be used as a thinner for most organic materials
- Will clean off adhesives including liquid, paste or gel anaerobics, UV adhesives and uncured plastics materials
- Brake disks and shoes
- Cleaning operations on electrical equipment**

* Always test cleaner on a small piece of plastic first

** Always switch off electrical equipment and unplug from mains before using a liquid cleaner



PART NUMBER:
63700M7019

TYPICAL CHARACTERISTICS



	Physical Characteristics*	Test Method
Physical Appearance	: Fluid	Visual
Colour	: Colourless	Visual
Odour	: Light, Characteristic	Smell
Specific Gravity At 25°C	: 0.742 g/ml	NFT 60.101
Boiling Point	: 43°C	ASTM D 1078
Auto Ignition Temperature	: >200°C	ASTM E 659
Freezing Point	: <-70°C	NFT 60.105
Viscosity At 25°C	: 0.766 mm ² /s	ASTM D445
Evaporation Rate (DEE=1)	: 3	DIN 53.170
KB Index	: 106	ASTM D 1133
Water Solubility	: <10 ppm	-
Surface Tension	: 12.8 dynes/cm	ASTM D 971
Copper Corrosion, 100h at 40°C	: 1a	ASTM D 1616
Discharge Rate	: 1.5 g/sec	-
Surface tension at 25C /dynes/cm	: Fastclean 200 – 12.8	1,1,1 Trichloroethane – 25.5
Packaging	: 400ml, 5, 25 and 200ltr packs also available	

APPLICATION METHOD

Shake can thoroughly before use. Hold upright 30 cm (12 inches) from surface to be treated. Spray and shake alternately until area is fully covered. Always switch off electrical equipment and unplug from mains before using a liquid cleaner. Eliminate all ignition sources when using the product.

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.