Paint & Graffiti Remover

making the difference

Technical Data

PAINT & GRAFFITI REMOVER is a highly effective solution to the difficult problem of removing graffiti. Particularly useful for hard, non-porous surfaces, such as walls, tiles, ceramics and metals, it quickly works on a variety of substances e.g. paint, ink, crayon, lipstick and grease.

DIRECTIONS

Shake can well before use. Apply an even coating from 9" - 12" (25 - 30 cm) and leave for 15 - 30 minutes. Wipe away with a soft, dry cloth, or hose away if possible. For stubborn soiling, repeat the process at regular intervals until the marks have been removed.

When treatment has been completed, wash the whole area with water and wipe away with a cloth or sponge.

N.B. May affect certain delicate or painted surfaces. Always test a small, inconspicuous area before general use.

PAINT AND GRAFFITI REMOVER PAINT AND GRAFFITI REMOVED PAINT AND GRAFFITI P

TECHNICAL DATA

Appearance : Clear, colourless liquid

Odour : Strong, sweet solvent

SG @ 20°C : 0.790

Pressure @ 20°C : 3 Bar

Discharge rate @ 20°C : 1.8 g/sec

Solubility : Miscible with water, soluble in most organic

solvents

Flammability : Classified as extremely flammable under

current EC Regulations

Flashpoint : Not applicable in sealed aerosol

Packaging : 400 ml aerosol (12 per carton)

PART NUMBER: 31630-AA







STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 12 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

Ambersil provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

