


Wall or Ceiling Mounted Pipe Clips



Product Data Sheet (2017-10-13)

BSI-HDI Clips

BSI-HDI clips are rubber lined, hot dip galvanized universal clips for mounting pipes to the wall or ceiling.



Type	Ø Pipe		Connection	Strip dimensions [mm]	Max. working load [N]	Dimensions			###	Order Code
	Ext. dia. [mm]	Nom. ["]				A [mm]	B [mm]	C [mm]		
BSI-HDI M 8/10 x 8 - 10	8 - 10	1/8	M 8/10	20 x 1.5	1000	53	13	16	50	38570
BSI-HDI M 8/10 x 12 - 14	12 - 14	1/4	M 8/10	20 x 1.5	1000	58	15	16	50	38571
BSI-HDI M 8/10 x 15 - 19	15 - 19	3/8	M 8/10	20 x 1.5	1000	62	18	16	50	38572
BSI-HDI M 8/10 x 20 - 25	20 - 25	1/2	M 8/10	20 x 1.5	1000	69	21	16	50	38573
BSI-HDI M 8/10 x 26 - 30	26 - 30	3/4	M 8/10	20 x 1.5	1000	74	23	16	50	38574
BSI-HDI M 8/10 x 32 - 36	32 - 36	1	M 8/10	20 x 1.5	1000	81	26	16	50	38575
BSI-HDI M 8/10 x 38 - 43	38 - 43	1 1/4	M 8/10	20 x 1.5	1000	87	30	16	50	38576
BSI-HDI M 8/10 x 44 - 49	44 - 49	1 1/2	M 8/10	20 x 1.5	1000	94	33	16	50	38577
BSI-HDI M 8/10 x 50 - 55	50 - 55		M 8/10	20 x 1.5	1000	103	36	16	50	38578
BSI-HDI M 8/10 x 56 - 61	56 - 61	2	M 8/10	20 x 1.5	1000	106	39	16	50	38579
BSI-HDI M 8/10 x 62 - 67	62 - 67		M 8/10	20 x 2.0	1300	113	42	16	50	38580
BSI-HDI M 8/10 x 68 - 73	68 - 73	2 1/4	M 8/10	20 x 2.0	1300	123	45	16	50	38581

Type	Ø Pipe		Connection	Strip dimensions [mm]	Max. working load [N]	Dimensions			###	Order Code
	Ext. dia. [mm]	Nom. ["]				A [mm]	B [mm]	C [mm]		
BSI-HDI M 8/10 x 75 - 80	75 - 80	2 1/2	M 8/10	20 x 2.0	1300	128	48	16	50	38582
BSI-HDI M 8/10 x 82 - 86	82 - 86	2 3/4	M 8/10	20 x 2.0	1300	134	51	16	50	38583
BSI-HDI M 8/10 x 87 - 92	87 - 92	3	M 8/10	20 x 2.0	1300	141	54	16	50	38584
BSI-HDI M 8/10 x 95 - 102	95 - 102	3 1/2	M 8/10	20 x 2.5	2150	158	58	16	50	38585
BSI-HDI M 8/10 x 108 - 116	108 - 116	4	M 8/10	20 x 2.5	2150	170	65	16	25	38586
BSI-HDI M 8/10 x 121 - 127	121 - 127		M 8/10	20 x 2.5	2150	185	70	16	25	38587
BSI-HDI M 8/10 x 131 - 141	131 - 141	5	M 8/10	20 x 2.5	2150	195	77	16	25	38588
BSI-HDI M 8/10 x 159 - 163	159 - 163		M 8/10	20 x 2.5	2150	215	88	16	25	38589
BSI-HDI M 8/10 x 165 - 169	165 - 169	6	M 8/10	20 x 2.5	2150	226	91	16	25	38590
BSI-HDI M 8/10 x 192 - 202	192 - 202		M 8/10	20 x 3.0	3000	265	107	16	25	38591
BSI-HDI M 8/10 x 210 - 220	210 - 220	8	M 8/10	20 x 3.0	3000	274	117	16	25	38592



Advantages

- The clip has one or more strengthening ribs to achieve a strong working load.
- Close fitting possible.

Technical information

- Hot-dip galvanized according to BS EN 1461:2009.
- Stainless steel bolts with slot and cross head and retaining ring.
- Noise-suppressing rubber lining according to ISO 3822-1.
(To achieve good sound suppression do not overload the fitting)<>
- Suitable for temperatures - 40 °C to + 120 °C.
- BSI-HDI clips are compatible with pipe sizes according to DIN 2448 and DIN EN 1057.
- Safety margin for minimal breaking load (V) = 3.